

Hovertechnics Inc**HOVERTOUR 1000 ORDER FORM**

<u>HVT No.</u>	<u>Description</u>	<u>Price</u> <u>(in US \$)</u>
7900200	<p>HOVERTOUR 1000 AIR CUSHION TRANSPORT VEHICLE powered by GM multi-port / fuel-injected 4-cycle, 350 cu. in. (5.7 liter), V-eight engine. Overall width of hard hull structure: 8' (2.44 m); overall length: 19'3" (5.87 m). 12v electrical system with 50 amp alternator. Dual 875 cca battery with battery master switch giving ON-1-BOTH-2 positions.</p> <p>Thrust system comprising: twin 39" (990 mm) ducted, twelve blade fans with air-straightener arrays driven by Goodyear Eagle Kevlar Vee tooth cog belts; ten cable-operated air rudders and removable fanguards. Hydraulically controlled splitter plates with handle-bar mounted electric push button switches allowing variable lift and thrust settings for speed and cushion control on the move. Electronic displays on instrument panel show position of splitters.</p> <p>Integrated lift and thrust air system with rough service skirts, rear mounted drag flap, six hardened aluminum replaceable skid rails. Fiberglass bottom hull made of hand lay-up woven roving plus sealed polyurethane foam liner with high freeboard sides. Winter windshield comprising rigid fiberglass, gelcoat structure with large curved windshield, two side windows with short roof; plus windshield wiper and washer system.</p> <p>Woven roving fiberglass inner hull with glossy gelcoat finish. Flat cockpit floor 5'x13' (150 cms x 400 cms) overall with 18" (46 cms) high cockpit sides.</p> <p>Standard Seating comprises center mounted pilot's cushion seat with backrest; one triangular side seat on each side of pilot; two two-person bench seats with back rests facing forwards.</p> <p>Fast-reaction handle bar steering, twist grip throttle, hinged access instrument panel with tachometer, hourmeter, engine oil pressure gauge and coolant temperature gauge, voltmeter; dual fuel gauges, 40 US gallon (150 l) capacity fuel tanks. Four mooring eyes and one bow eye. Twin fiberglass tail fin style wave guards and splashguards.</p> <p>Twin strobe flashers (amber), white all-round light on ducts; red/green bow light and operating lights; two 2,000 gph bilge pumps.</p> <p>Payload with standard equipment: 1,200 lbs. (544 kgs)</p> <p>Choice of hull colors: RED WHITE YELLOW BLUE</p> <p>List Price ex-factory Eau Claire, Michigan</p>	67,800.00

Hovertechnics Inc

HOVERTOUR 1000 ORDER FORM (cont.)

Optional Equipment:

7900302	Non-Standard Color - inner hull gelcoat surfaces in customer's special color. Cockpit floor in black unless otherwise requested.	600.00
304	Rear Cockpit Enclosure - vinyl enclosure with clear vinyl side and rear windows and quick release snap fasteners, over tubular aluminum frame. Zip-in panels.	1,450.00
311	All Kevlar Bottom Hull	2,153.00
327	Heater-Defroster - marine heater core and fan unit directly connected to engine cooling system with protected hoses and equipped with adjustable outlets on instrument panel directed at windshield.	700.00
328	Lift Eyes - for raising complete craft with davits or crane/hoist	985.00
329	Stainless Steel Dual Muffler - in place of standard tin coated pipes and muffler.	825.00
331	90 AMP Alternator – i.p.o. 50 amp standard alternator, both with built-in voltage regulator.	standard
332	Operating Light Package - four 100 watt x 12v off-highway halogen lights mounted on winter windshield and switched in pairs.	510.00
333	Stationary Hover System – consists of variable angled metal plates between the nose cones and rudders; these serve to block the thrust airflow to the rear whilst still allowing the lift air to raise the craft up to the maximum hoverheight in the stationary position. Electric over hydraulic, handlebar mounted push-button controls; electronic position displays on instrument panel.	1,770.00
334	Special Options	on request
336	Thunder 29 Hearing Protection Muffs	29.50
337	Mustang Survival Suits and Vests	on request
338	Aluminum Decking over basic floor to withstand impact loads	985.00

Delivery: upon request

Payment Terms: forty (40%) percent with order by check or wire transfer;
balance due by cashier's check or wire transfer at time of completion.

specifications and prices are subject to change without notice