

Effective: 1 January 2009

**HOVERTECHNICS INC**  
**HOVERTOUR 2000 ORDER FORM**

<u>HVT</u>	<u>Description</u>	<u>Price in</u> <u>US\$</u>
------------	--------------------	--------------------------------

7900100

**HOVERTOUR 2000 AIR CUSHION TRANSPORT VEHICLE** powered by GM V 8 multi-port / fuel injected four-cycle, 350 cu. in. (5.7 liter) engine, electronic ignition, 250 HP at sea level; 12v electrical system with 90 amp alternator. Dual 875 cca batteries with battery master switch giving OFF-1-Both-2 positions.

**Hull Length 21' 3" (6.48 m)      Width: 8 ft. (2.44 m)**

**Thrust system** comprising: twin 39" (990 mm) ducted, twelve blade fans with air-straightener arrays driven by Goodyear Eagle Kevlar Vee tooth cog belts; ten cable-operated air rudders and removable fanguards. Hydraulically controlled splitter plates with handle bar mounted electric push button switches allowing variable lift / thrust settings for speed and cushion control on the move. Electronic displays on instrument panel show position of splitters.

**Integrated lift and thrust air system** with hypalon skirts, rear mounted drag flap, six hardened aluminum replaceable skid rails. **KEVLAR** bottom hull made entirely of hand lay-up woven Kevlar plus sealed polyurethane foam liner with high freeboard sides.

**Woven roving fiberglass** inner hull with glossy gelcoat finish. Flat cockpit floor 5' x 15' overall with 18" high cockpit sides. All-weather windshield comprising rigid fiberglass, gelcoat structure with large curved windshield, two side windows with short roof; plus windshield wiper and washer system.

**Standard Seating** comprises center mounted pilot's cushion seat with backrest; one triangular side seat on each side of pilot; centerline back to back bench seat for six persons facing sideways; total 9 seats not exceeding 1,500 lbs. payload.

**Fast-reaction handle bar steering**, twist grip throttle; hinged access instrument panel with tachometer, hourmeter, engine oil pressure gauge and coolant temperature gauge; voltmeter, dual fuel gauges, 40 US gallon (150 l) capacity fuel tanks. Four mooring eyes, one bow eye and one rear winching eye. Twin fiberglass tail fin style waveguards and splashguards.

**Twin strobe flashers** (amber), white all-round light on ducts; red/green bow light. Two 5' grab rails, two collapsible grapple poles.

**Payload** with standard equipment listed above: 1,500 lbs.(682 kg)

**List Price ex-factory Eau Claire, Michigan:**

**83,500.00**

Effective: 1 January 2009

**HOVERTECHNICS INC**  
**HOVERTOUR 2000 ORDER FORM (cont.)**

	<b>Choice of Hull Colors:</b> RED WHITE YELLOW BLUE	
	<b>Optional Equipment:</b>	
302	<b>Non-Standard Color</b> – inner hull gelcoat surfaces in customer's special color. Cockpit floor in black.	700.00
304	<b>Rear Cockpit Vinyl Enclosure</b> w. clear vinyl side windows & quick release snap fasteners over tubular aluminum frame. Zip-in panels.	1,630.00
327	<b>Heater / Defroster</b> – marine heater core and fan unit directly connected to engine cooling system with protected hoses and equipped with adjustable outlets on instrument panel directed at windshield.	700.00
328	<b>Lift Eyes</b> – for raising complete craft with davits or crane/hoist	985.00
329	<b>Stainless Steel Dual Muffler</b> i.p.o. standard aluminized pipes and muffler.	825.00
332	<b>Operating Light Package</b> – four 100 watt x 12 v off-highway halogen lights mounted on winter windshield and switched in pairs.	510.00
333	<b>Stationary Hover System</b> – i.p.o. straightener array behind fans. Electric over hydraulic, handlebar mounted push-button controls; electronic position displays on instrument panel.	1,770.00
334	<b>Special Options</b>	on request
336	<b>Thunder 29</b> Hearing Protection Muffs	29.50
337	<b>Mustang</b> Survival Suits and Vests	on request
338	<b>Aluminum Decking</b> over basic floor to withstand impact loads	1,185.00

Delivery: upon request

Payment: forty (40%) percent with order by check or wire transfer;  
balance due by cashier's check or wire transfer upon completion.

**specifications and prices are subject to change without notice.**