

*Hovertechnics Inc***HOVERTOUR 800 ORDER FORM**

<u>HVT No.</u>	<u>Description</u>	<u>Price</u> <u>(in US \$)</u>
----------------	--------------------	-----------------------------------

7900300	<p>HOVERTOUR 800 AIR CUSHION TRANSPORT VEHICLE powered by GM multi-port / fuel-injected 4-cycle, 5.7 liter V-8 engine. Overall width of hard structure: 8' (2.44 m); Overall length: 16' (4.88 m). 12v electrical system with 50 amp alternator. Dual 875 cold cranking amp batteries with battery master switch giving OFF-1-BOTH-2 positions.</p>	
---------	--	--

Thrust system comprising twin 39" (990 mm) ducted 12 blade fans with air straightener arrays driven by Goodyear Eagle Kevlar Vee tooth cog belts; ten cable-operated air rudders and removable fanguards. Hydraulically controlled splitter plates with handle bar mounted electric push button switches allowing variable lift and thrust settings for speed and cushion control on the move. Electronic displays on instrument panel show position of splitters.

Integrated lift and thrust air system with rough service skirts, rear mounted drag flap, six hardened aluminum replaceable skid rails. Fiberglass bottom hull made of hand lay-up woven roving plus sealed polyurethane foam liner with high freeboard sides.

Woven roving fiberglass inner hull with glossy gelcoat finish. Flat cockpit floor 5' x 10' (150 cms x 305 cms) overall with 18" (46 cms) high cockpit sides. Two triangular vinyl cushion seats mounted one on each side of pilot's seat. Two cushion seats with hinged backrests behind.

Combined winter front and windshield comprising rigid fiberglass gelcoat structure with large curved windshield, two side windows with short roof plus windshield wiper and washer system.

Fast-reaction handle bar steering, twist grip throttle; hinged access instrument panel with tachometer, hourmeter, engine oil pressure gauge and coolant temperature gauge, voltmeter and fuel gauges; 40 US gallon capacity fuel tanks. Four mooring eyes, one bow eye and one rear winching eye. Twin fiberglass tail fin style wave guards and splashguards.

Twin strobe flashers (amber), white all-round light on ducts; red/green bow light and operating lights; two 2,000 gph bilge pumps.

Payload with standard equipment listed above: 850 lbs. (385 kgs)

Choice of hull colors: RED WHITE YELLOW BLUE

List Price ex-factory Eau Claire, Michigan

55,400.00

- more -

Hovertechnics Inc
HOVERTOUR 800 ORDER FORM (cont.)

<u>HVT No.</u>	<u>Description - Optional Equipment</u>	<u>Price</u> <u>(in US \$)</u>
7900302	Non-Standard Color - inner hull gelcoat surfaces in customer's special color. Cockpit floor in black unless otherwise requested.	500.00
304	Rear Cockpit Enclosure - vinyl enclosure with clear vinyl side windows and quick release snap fasteners, over tubular aluminum frame. Zip-in panels. Note: recommended for winter operation only	1,350.00
311	All Kevlar Bottom Hull	1,785.00
327	Heater-Defroster - marine heater core and fan unit directly connected to engine cooling system with protected hoses and equipped with adjustable outlets on instrument panel directed at windshield.	700.00
328	Lift Eyes - for raising complete craft with davits or crane/hoist	985.00
329	Stainless Steel Dual Muffler - in place of standard aluminized pipes and muffler.	825.00
331	90 AMP Alternator - in place of 50 amp standard alternator, both with built-in voltage regulator.	standard
332	Operating Light Package – four 100 watt x 12 v off-highway halogen lights mounted on winter windshield and switched in pairs.	510.00
333	Stationary Hover System - consists of variable angled metal plates between the nose cones and rudders; these serve to block the thrust airflow to the rear whilst still allowing the lift air to raise the craft up to the maximum hoverheight in the stationary position. Electric over hydraulic, handlebar mounted push-button controls; electronic position displays on instrument panel.	1,770.00
334	Special Options available on request - intercom/radio equipment, special seating:	on request
336	Thunder 29 Hearing Protection Muffs	29.50
337	Mustang Survival Suits and Vests	on request
338	Aluminum Decking over basic floor to withstand impact loads	850.00

Delivery: upon request

Payment Terms: forty (40%) percent with order (enclose check please);
balance due by cashier's check or wire transfer at time of completion.

specifications and prices are subject to change without notice