

Hovertechnics Inc

HOVERGUARD 1000 Order Form

<u>HVT No.</u>	<u>Description</u>	<u>Price</u> <u>(in US\$)</u>
7900200	<p>HOVERGUARD 1000 AIR CUSHION RESCUE VEHICLE powered by General Motors 4-cycle, 350 cu. in. (5.7 liter) V-8 multi-port / fuel injected engine. Overall width of hard hull structure: 8' (2.44 m); Overall length: 19'3" (5.87 m). 12v electrical system with 90 amp alternator. Dual 875 cold cranking amp batteries with battery master switch giving OFF-1-BOTH-2 positions.</p> <p>Thrust frame comprising twin 39" (990 mm) ducted, twelve blade fans with air straightener arrays driven by Goodyear Eagle Kevlar core Vee tooth cog belts; ten cable-operated air rudders and removable fanguards. Hydraulically controlled splitter plates with handle bar mounted electric push button switches allowing variable lift and thrust settings for speed and cushion control on the move. Electronic displays on instrument panel show position of splitters.</p> <p>Integrated lift and thrust air system with hypalon-coated skirts, rear mounted drag flap, six hardened aluminum replaceable skid rails. Winter windshield comprising rigid fiberglass, gelcoat structure with large curved windshield, two side windows with short roof; plus windshield wiper and washer system.</p> <p>Woven roving fiberglass inner hull with glossy gelcoat finish. Flat cockpit floor 5' x 13' (150 cms x 400 cms) overall with 18" (46 cms) high cockpit sides. Two triangular vinyl cushion seats mounted one on each side of 4' (122 cms) long centerline padded crew seat.</p> <p>Fast-reaction handle bar steering, twist grip throttle; hinged access instrument panel with tachometer, hourmeter, engine oil pressure gauge and coolant temperature gauge, voltmeter; dual fuel gauges, 40 US gallon (150 l) capacity fuel tanks. Four mooring eyes, one bow eye and one rear winching eye. Twin fiberglass tail fin style waveguards and splashguards.</p> <p>Twin strobe flashers (red, blue or amber), white all-round light on ducts; red/green bow light. Side-mounted grab rails, two collapsible grapple poles, two ring buoys.</p> <p>Payload with standard equipment listed above: 1,200 lbs. (544 kgs)</p> <p>Choice of hull colors: RED WHITE YELLOW List Price ex-factory Eau Claire, Michigan</p>	69,200.00
<u>Optional Equipment:</u>		
7900302	<p>Non-Standard Color - inner hull gelcoat surfaces in customer's special color. Cockpit floor in black unless otherwise requested.</p>	600.00

Hovertechnics Inc

HOVERGUARD 1000 Order Form (cont.)

<u>HVT No.</u>	<u>Description</u>	<u>Price (in US \$)</u>
304	Rear Cockpit Enclosure - vinyl enclosure with clear vinyl side windows and quick release snap fasteners, over tubular aluminum frame. Zip-in panels.	1,450.00
311	All Kevlar Bottom Hull	2,153.00
321	Combined Siren and Public Address System - comprising 100 watt amplifier with 3 siren tones, noise reducing microphone and 100 watt wide angle speaker.	1,350.00
327	Heater-Defroster - marine heater core and fan unit directly connected to engine cooling system with protected hoses and equipped with adjustable outlets on instrument panel directed at windshield.	700.00
328	Lift Eyes - for raising complete craft with davits or crane/hoist	985.00
329	Stainless Steel Dual Muffler - in place of standard aluminized pipes and muffler.	825.00
331	90 AMP Alternator - in place of 50 amp standard alternator, both with built-in voltage regulator.	standard
332	Night Rescue Lighting Package - four 100 watt x 12v off-highway halogen lights mounted on winter windshield and switched in pairs.	510.00
333	Stationary Hover System - in place of straightener array behind fans. Electric over hydraulic, handlebar mounted push-button controls; electronic position displays on instrument panel.	1,770.00
334	Special Options available upon request - GPS system, 48" police style light bar; dive tank stowage mountings, intercom/radio equipment, special seating:	on request
335	Interior Cockpit Lighting:	725.00
336	Thunder 30 Hearing Protection Muffs	each 29.50
337	Mustang Survival Suits and Vests	on request
338	Aluminum Decking over basic floor to withstand impact loads	985.00

Delivery: upon request

Payment Terms: forty (40%) percent deposit with order (please enclose check);
balance by cashier's check or wire transfer at time of completion

specifications and prices are subject to change without notice