

**Hovertechnics Inc****HOVERGUARD 800 Order Form**

<u>HVT No.</u>	<u>Description</u>	<u>Price</u> <u>(in US \$)</u>
----------------	--------------------	-----------------------------------

7900300	<b>HOVERGUARD 800 AIR CUSHION RESCUE</b>	
---------	------------------------------------------	--

**VEHICLE** powered by General Motors 4-cycle, 5.7 liter V-8 multi-port / fuel injected engine. Overall width of hard structure: 8' (2.44 m); Overall length: 16' (4.88 m). 12v electrical system with 90 amp alternator. Dual 875 cold cranking amp batteries with battery master switch giving OFF-1-BOTH-2 positions.

**Thrust system comprising** twin 39" (990 mm) ducted 12 blade fans with air straightener arrays driven by Goodyear Eagle Kevlar Vee tooth cog belts; ten cable-operated air rudders and removable fanguards. Hydraulically controlled splitter plates with handle bar mounted electric push button switches allowing variable lift and thrust settings for speed and cushion control on the move. Electronic displays on instrument panel show position of splitters.

**Integrated lift and thrust air system** with Hypalon-coated skirts, rear mounted drag flap, six hardened aluminum replaceable skid rails. Fiberglass bottom hull made of hand lay-up woven roving plus sealed polyurethane foam liner with high freeboard sides.

**Woven roving fiberglass** inner hull with glossy gelcoat finish. Flat cockpit floor 5' x 10' (150 cms x 305 cms) overall with 18" (46 cms) high cockpit sides. Two triangular vinyl cushion seats mounted one on each side of centerline cushion crew seat and stowage module.

**Combined winter front and windshield** comprising rigid fiberglass gelcoat structure with large curved windshield, two side windows with short roof plus windshield wiper and washer system.

**Fast-reaction handle bar steering**, twist grip throttle; hinged access instrument panel with tachometer, hourmeter, engine oil pressure gauge and coolant temperature gauge, voltmeter and fuel gauges; 40 US gallon capacity fuel tanks. Four mooring eyes, one bow eye and one rear winching eye. Twin fiberglass tail fin style wave guards and splash guards.

Twin strobe flashers (red, blue or amber), white all-round light on ducts; red/green bow light. Two 5' grab rails, two collapsible grapple poles, two ring buoys.

Payload with standard equipment listed above: 850 lbs. (385 kgs)

Choice of hull colors:            RED            WHITE            YELLOW

**List Price ex-factory Eau Claire, Michigan**

**56,750.00**

- more -

*Hovertechnics Inc***HOVERGUARD 800 Order Form (cont.)**

<u>HVT No.</u>	<u>Description - Optional Equipment</u>	<u>Price (in US \$)</u>
7900302	<b>Non-Standard Color</b> - inner hull gelcoat surfaces in customer's special color. Cockpit floor in black unless otherwise requested.	500.00
304	<b>Rear Cockpit Enclosure</b> — vinyl enclosure with clear vinyl side windows and quick release snap fasteners, over tubular aluminum frame. Zip-in panels. Recommended for winter operation only.	1,350.00
311	<b>All Kevlar Bottom Hull</b>	1,785.00
321	<b>Combined Siren and Public Address System</b> - comprising 100 watt amplifier with 3 siren tones, noise reducing microphone and 100 watt wide angle speaker.	1,350.00
327	<b>Heater-Defroster</b> - marine heater core and fan unit directly connected to engine cooling system with protected hoses and equipped with adjustable outlets on instrument panel directed at windshield.	700.00
328	<b>Lift Eyes</b> - for raising complete craft with davits or crane/hoist	985.00
329	<b>Stainless Steel Dual Muffler</b> - in place of standard aluminized pipes and muffler.	825.00
331	<b>90 AMP Alternator</b> - in place of 50 amp standard alternator, both with built-in voltage regulator.	standard
332	<b>Night Rescue Lighting Package</b> - four 100 watt x 12v off-highway halogen lights mounted on winter windshield and switched in pairs.	510.00
333	<b>Stationary Hover System</b> - in place of straightener array behind fans. Electric over hydraulic, handlebar mounted push-button controls; electronic position displays on instrument panel.	1,770.00
334	<b>Special Options available on request</b> - GPS system, 48" police style light bar, dive tank stowage mountings, intercom/radio equipment, special seating;	on request
335	<b>Interior Cockpit Lighting:</b>	610.00
336	<b>Thunder 30</b> Hearing Protection Muffs	each 29.50
337	<b>Mustang Survival Suits and Vests</b>	on request
338	<b>Aluminum Decking over basic floor to withstand impact loads</b>	850.00

Delivery: upon request

Payment Terms: forty (40%) percent deposit with order (enclose check please);  
balance by cashier's check or wire transfer at time of completion.

**specifications and prices are subject to change without notice**